

NSN 5963-00-401-4265 Noncrystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5963-00-401-4265 **Overall Length:** 1.750 inches **Overall Height:** 0.600 inches **Overall Width:** 1.250 inches **Environmental Protection:** Dustproof **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** -20.0 to 71.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Hermetically sealed Installation Design: Module **Circuit Construction Type:** Solid state **Frequency Per Channel:**

59.9 megahertz output channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

600.000 millivolts output

Overall Gain:

Not rated

Impedance Rating Per Channel:

50.000 ohms output channel

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Printed circuit bottom

NSN 5963-00-401-4265

Noncrystal Controlled Oscillator - Page 2 of 2



Connection Contact Type And Quantity:

4 printed circuit external

External Dc Operating Voltage In Volts:

12.0 single voltage

Fsc Application Data:

Inverter, spectrum, test station, guided missile remote control system

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200