NSN 5963-00-406-1838

Noncrystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5963-00-406-1838



Overall Length: 4.812 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** +0.0 to 65.0 degrees celsius **Average Life Rating:** 87600.0 **Average Life Measurement: Average Life Rating In Hours:** 87600.0 **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased Installation Design: Module **Circuit Construction Type:** Solid state Frequency Per Channel: 18.0 kilohertz output channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated **Signal Voltage Rating Per Channel:** 3.000 volts output **Overall Gain:** Not rated Impedance Rating Per Channel: 100.000 ohms output channel

Frequency Per Channel:

18.0 kilohertz output channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

3.000 volts output

Overall Gain:

Not rated

Impedance Rating Per Channel:

100.000 ohms output channel

Distortion Type And Percent:

0.1 frequency

NSN 5963-00-406-1838

Noncrystal Controlled Oscillator - Page 2 of 2



Maximum Continuous Operating Time In Hours:

200000.0

Connection Type And Location:

Receptacle, power bottom

Connection Contact Type And Quantity:

8 receptacle, power external

External Dc Operating Voltage In Volts:

28.0 single voltage

Special Features:

Output level control

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32200