NSN 5963-01-023-9402

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-023-9402

| Overall Length: |
|---|
| 2.620 inches |
| Overall Height: |
| 0.290 inches |
| Overall Width: |
| 1.950 inches |
| Environmental Protection: |
| Salt spray resistant and vibration |
| Operating Tempurature Range: |
| +0.0/+60.0 degrees celsius |
| Average Life Rating: |
| 500.0 |
| Storage Tempurature Range: |
| -62.0/+125.0 degrees celsius |
| Average Life Measurement: |
| Hours |
| Average Life Rating In Hours: |
| 500.0 |
| Basic Shape Style: |
| Rectangular or square |
| Inclosure Type: |
| Encased |
| Operating Control Method: |
| Automatic |
| Installation Design: |
| Module |
| Control Type: |
| Remote |
| Circuit Construction Type: |
| Solid state |
| Signal Voltage Rating Per Channel: |
| 800.000 millivolts interstage |
| Signal Data Type Per Channel: |
| 2nd output channel digital err-100 |
| Connection Type And Location: |
| Connector, plug bottom |
| Connection Contact Type And Quantity: |
| 1 connector, plug external |
| External Dc Operating Voltage In Volts: |
| 5.0 single voltage |
| Special Features: |
| Key code kdn |

NSN 5963-01-023-9402

Standardized Electronic Module - Page 2 of 2



Special Markings:

Receiver, differential line, digital

Test Data Document:

81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-28787/53 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200