

NSN 5963-01-024-8050 Standardized Electronic Module - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5963-01-024-8050 **Overall Length:** 2.620 inches **Overall Height:** 0.290 inches **Overall Width:** 1.950 inches **Environmental Protection:** Salt spray resistant and vibration **Operating Tempurature Range:** +0.0/+60.0 degrees celsius **Average Life Rating:** 500.0 **Storage Tempurature Range:** -62.0/+125.0 degrees celsius **Average Life Measurement:** Hours **Average Life Rating In Hours:** 500.0 **Basic Shape Style:** Rectangular or square **Inclosure Type:** Encased **Operating Control Method:**

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

6.6 megahertz operating channel

Signal Voltage Rating Per Channel:

500.000 millivolts interstage preset

Signal Data Type Per Channel:

Operating channel radio frequency err-100

Connection Type And Location:

Connector, plug bottom

Maximum Power Drain Rating:

330.0 milliwatts

Connection Contact Type And Quantity:

1 connector, plug external

NSN 5963-01-024-8050

Standardized Electronic Module - Page 2 of 2



External Dc Operating Voltage In Volts:
5.0 single voltage
Special Features:
Key code qvg
Special Markings:
Oscillator, crystal, digital
Test Data Document:
81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-28787/235 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A32200