NSN 5963-01-026-2796

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-026-2796
Overall Length:
2.620 inches
Overall Height:
0.290 inches
Overall Width:
1.950 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Rating:
500.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
500.0
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Signal Voltage Rating Per Channel:

3.500 volts input preset and 5.500 volts interstage preset

Signal Data Type Per Channel:

2nd input channel analog voltage err-100

Connection Type And Location:

Connector, plug bottom

Maximum Power Drain Rating:

715.0 milliwatts

Connection Contact Type And Quantity:

1 connector, plug external

External Dc Operating Voltage In Volts:

5.0 1st voltage err-100

NSN 5963-01-026-2796

Fiig: A32200

Standardized Electronic Module - Page 2 of 2



Special Features:
Key code vgs
Special Markings:
Demultiplexer, analog
Test Data Document:
81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-28787/182 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli