NSN 5963-01-045-1316

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-045-1316
Overall Length:
2.620 inches
Overall Height:
0.590 inches
Overall Width:
1.950 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Rating:
500.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
500.0
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Signal Voltage Rating Per Channel:
Between 1.400 volts input and 4.500 volts interstage
Signal Data Type Per Channel:
2nd input channel analog voltage err-100
Connection Type And Location:
Connector, plug hottom

Maximum Power Drain Rating:

2.0 watts

Connection Contact Type And Quantity:

2 connector, plug external

External Dc Operating Voltage In Volts:

8.0 2nd voltage err-100

NSN 5963-01-045-1316

A32200

Standardized Electronic Module - Page 2 of 2



Special Features:
Key code npm
Special Markings:
Relay, dpdt, power
Test Data Document:
81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-28787/38 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: