Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-047-1766

Overall Length:	
2.620 inches	
Overall Height:	
0.290 inches	
Overall Width:	
1.950 inches	
Environmental Protection:	
Salt spray resistant and vibration	
Operating Tempurature Range:	
+0.0/+60.0 degrees celsius	
Average Life Rating:	
500.0	
Storage Tempurature Range:	
-62.0/+125.0 degrees celsius	
Average Life Measurement:	
Hours	
Average Life Rating In Hours:	
500.0	
Basic Shape Style:	
Rectangular or square	
Inclosure Type:	
Encased	
Operating Control Method:	
Automatic	
Installation Design:	
Module	
Control Type:	
Remote	
Circuit Construction Type:	
Solid state	
Frequency Per Channel:	
20.0 megahertz operating channel	
Signal Voltage Rating Per Channel:	
800.000 millivolts interstage	
Pulse Duration Per Channel:	
20.000 nanoseconds operating channel	I
Signal Data Type Per Channel:	
Operating channel radio frequency err-1	00
Connection Type And Location:	
Connector, plug bottom	
Maximum Power Drain Rating:	
1.9 watts	



Connection Contact Type And Quantity:

1 connector, plug external

External Dc Operating Voltage In Volts:

5.0 single voltage

Special Features:

Key code gdm

Special Markings:

Counter, up and down, binary

Test Data Document:

81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-28787/27 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200