

View Online at <https://aerobasegroup.com/nsn/5963-01-057-8482>

**Overall Length:**

2.620 inches

**Overall Height:**

1.950 inches

**Overall Width:**

0.290 inches

**Environmental Protection:**

Salt spray resistant and vibration

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Average Life Rating:**

500.0

**Storage Temperature Range:**

-62.0/+125.0 degrees celsius

**Average Life Measurement:**

Hours

**Average Life Rating In Hours:**

500.0

**Basic Shape Style:**

Rectangular or square

**Inclosure Type:**

Encased

**Operating Control Method:**

Automatic

**Installation Design:**

Module

**Control Type:**

Remote

**Circuit Construction Type:**

Solid state

**Signal Voltage Rating Per Channel:**

2.400 volts any acceptable 2.400 volts any acceptable 2.400 volts any acceptable 2.400 volts any acceptable 2.400 volts any acceptable

2.400 volts any acceptable 2.400 volts any acceptable 2.400 volts any acceptable

**Signal Data Type Per Channel:**

1st input channel analog voltage err-100 2nd input channel analog voltage err-100 3rd input channel analog voltage err-100 4th input channel analog voltage err-100 5th input channel analog voltage err-100 6th input channel analog voltage err-100 7th input channel analog voltage err-100 8th input channel analog voltage err-100

**Connection Type And Location:**

Connector, plug bottom

**Maximum Power Drain Rating:**

800.0 milliwatts

**Connection Contact Type And Quantity:**

1 connector, plug external

**External Dc Operating Voltage In Volts:**

-15.0 1st voltage err-100 15.0 2nd voltage err-100

**Special Features:**

Key code tsy

**Special Markings:**

Analog switch

**Test Data Document:**

10001-2833417 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32200