NSN 5963-01-057-8549

Overall Length:

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-057-8549

Overall Height:
0.000 ! !
0.290 inches
Overall Width:
1.950 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Rating:
500.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
500.0
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Module Control Type:
Control Type:
Control Type: Local
Control Type: Local Circuit Construction Type:
Control Type: Local Circuit Construction Type: Solid state
Control Type: Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel:
Control Type: Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 400.000 millivolts interstage
Control Type: Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 400.000 millivolts interstage Signal Data Type Per Channel:
Control Type: Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 400.000 millivolts interstage Signal Data Type Per Channel: 2nd operating channel digital err-100
Control Type: Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 400.000 millivolts interstage Signal Data Type Per Channel: 2nd operating channel digital err-100 Connection Type And Location:
Control Type: Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 400.000 millivolts interstage Signal Data Type Per Channel: 2nd operating channel digital err-100 Connection Type And Location: Connector, plug bottom
Control Type: Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 400.000 millivolts interstage Signal Data Type Per Channel: 2nd operating channel digital err-100 Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating:
Control Type: Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 400.000 millivolts interstage Signal Data Type Per Channel: 2nd operating channel digital err-100 Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 969.0 milliwatts
Control Type: Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 400.000 millivolts interstage Signal Data Type Per Channel: 2nd operating channel digital err-100 Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 969.0 milliwatts Connection Contact Type And Quantity:

NSN 5963-01-057-8549

A32200

Standardized Electronic Module - Page 2 of 2



Special Features:
Key code fyd
Special Markings:
Read-only memory
Test Data Document:
10001-2833569 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig: