

View Online at <https://aerobasegroup.com/nsn/5963-01-057-8563>

Overall Length:

2.620 inches

Overall Height:

0.290 inches

Overall Width:

1.950 inches

Environmental Protection:

Salt spray resistant and vibration

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Average Life Rating:

500.0

Storage Temperature Range:

-62.0/+125.0 degrees celsius

Average Life Measurement:

Hours

Average Life Rating In Hours:

500.0

Basic Shape Style:

Rectangular or square

Inclosure Type:

Encased

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Signal Voltage Rating Per Channel:

400.000 millivolts interstage

Pulse Duration Per Channel:

10.000 nanoseconds operating channel

Pulse Rise Time Per Channel:

100.000 nanoseconds operating channel

Pulse Decay Time Per Channel:

100.000 nanoseconds operating channel

Pulse Peak Amplitude Per Channel:

500.000 millivolts operating channel

Signal Data Type Per Channel:

2nd output channel digital err-100

Connection Type And Location:

Connector, plug bottom

Maximum Power Drain Rating:

969.0 milliwatts

Connection Contact Type And Quantity:

1 connector, plug external

External Dc Operating Voltage In Volts:

-12.0 1st voltage err-100

Special Features:

Key code gyn

Special Markings:

Read-only memory module

Test Data Document:

10001-2833534 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200