NSN 5963-01-057-8613

Overall Length: 2.620 inches Overall Height: 0.290 inches Overall Width:

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-057-8613

1.950 inches									
Environmental Protection:									
Salt spray resistant and vibration									
Operating Tempurature Range:									
+0.0/+60.0 degrees celsius									
Average Life Rating:									
500.0									
Storage Tempurature Range:									
-62.0/+125.0 degrees celsius									
Average Life Measurement:									
Hours									
Average Life Rating In Hours:									
500.0									
Basic Shape Style:									
Rectangular or square									
Inclosure Type:									
Encased									
Operating Control Method:									
Automatic									
Installation Design:									
Module									
Control Type:									
Local									
Local									
Local Circuit Construction Type:									
Local Circuit Construction Type: Solid state									
Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel:									
Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 800.000 millivolts interstage									
Local Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 800.000 millivolts interstage Signal Data Type Per Channel:									
Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 800.000 millivolts interstage Signal Data Type Per Channel: 4th input channel digital err-100									
Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 800.000 millivolts interstage Signal Data Type Per Channel: 4th input channel digital err-100 Connection Type And Location:									
Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 800.000 millivolts interstage Signal Data Type Per Channel: 4th input channel digital err-100 Connection Type And Location: Connector, plug bottom									
Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 800.000 millivolts interstage Signal Data Type Per Channel: 4th input channel digital err-100 Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity:									
Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 800.000 millivolts interstage Signal Data Type Per Channel: 4th input channel digital err-100 Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity: 1 connector, plug external									
Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 800.000 millivolts interstage Signal Data Type Per Channel: 4th input channel digital err-100 Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts:									
Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 800.000 millivolts interstage Signal Data Type Per Channel: 4th input channel digital err-100 Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.0 2nd voltage err-100									

NSN 5963-01-057-8613

Standardized Electronic Module - Page 2 of 2



	u	_	a	W	а	ш	N	u	3	
_	-							J	_	

Read-only memory

Test Data Document:

10001-2833423 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200