

NSN 5963-01-057-8618 Standardized Electronic Module - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5963-01-057-8618 **Overall Length:** 2.620 inches **Overall Height:** 0.590 inches **Overall Width:** 1.950 inches **Environmental Protection:** Salt spray resistant and vibration **Operating Tempurature Range:** +0.0/+60.0 degrees celsius **Average Life Rating:** 500.0 **Storage Tempurature Range:** -62.0/+125.0 degrees celsius **Average Life Measurement:** Hours **Average Life Rating In Hours:** 500.0 **Basic Shape Style:** Rectangular or square **Inclosure Type:** Encased

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

400.0 hertz input channel

Signal Voltage Rating Per Channel:

115.000 volts input

Signal Data Type Per Channel:

Operating channel analog voltage

Connection Type And Location:

Connector, plug bottom

Maximum Power Drain Rating:

510.0 milliwatts

Connection Contact Type And Quantity:

1 connector, plug external

NSN 5963-01-057-8618

Yes - demil/mli

Fiig: A32200

Standardized Electronic Module - Page 2 of 2



| External Dc Operating Voltage In Volts: |
|--|
| -15.0 1st voltage err-100 |
| Special Features: |
| Key code umw |
| Special Markings: |
| Reference transformer |
| Test Data Document: |
| 10001-2833509 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |