Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-062-2195

Overall Length:
2.620 inches
Overall Height:
0.290 inches
Overall Width:
1.950 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Rating:
500.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
500.0
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
15.0 megahertz operating channel
Signal Voltage Rating Per Channel:
400.000 millivolts input preset
Pulse Duration Per Channel:
40.000 nanoseconds operating channel
Pulse Peak Amplitude Per Channel:
3.000 volts operating channel
Signal Data Type Per Channel:
Operating channel radio frequency err-100
Connection Type And Location:
Connector, plug bottom



Maximum Power Drain Rating:

1.7 watts

Connection Contact Type And Quantity:

1 connector, plug external

External Dc Operating Voltage In Volts:

5.0 single voltage

Special Features:

Key code jdd

Special Markings:

Counter, up/down, bcd, presettable

Test Data Document:

81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-28787/31 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200