## NSN 5963-01-066-6959

Overall Length: 2.620 inches

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-066-6959

Overall Height:
1.950 inches
Overall Width:
0.290 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Rating:
500.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
500.0
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Automatic Installation Design:
Installation Design:
Installation Design: Module
Installation Design:  Module  Control Type:
Installation Design: Module Control Type: Remote
Installation Design: Module Control Type: Remote Circuit Construction Type:
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel:
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: Between 2.400 volts input and 5.500 volts interstage
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: Between 2.400 volts input and 5.500 volts interstage Signal Data Type Per Channel:
Installation Design:  Module  Control Type:  Remote  Circuit Construction Type:  Solid state  Signal Voltage Rating Per Channel:  Between 2.400 volts input and 5.500 volts interstage  Signal Data Type Per Channel:  Output channel analog voltage err-100
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: Between 2.400 volts input and 5.500 volts interstage Signal Data Type Per Channel: Output channel analog voltage err-100 Connection Type And Location:
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: Between 2.400 volts input and 5.500 volts interstage Signal Data Type Per Channel: Output channel analog voltage err-100 Connection Type And Location: Connector, plug bottom
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: Between 2.400 volts input and 5.500 volts interstage Signal Data Type Per Channel: Output channel analog voltage err-100 Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity:
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: Between 2.400 volts input and 5.500 volts interstage Signal Data Type Per Channel: Output channel analog voltage err-100 Connection Type And Location: Connector, plug bottom Connector, plug external
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: Between 2.400 volts input and 5.500 volts interstage Signal Data Type Per Channel: Output channel analog voltage err-100 Connection Type And Location: Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts:

## NSN 5963-01-066-6959

Standardized Electronic Module - Page 2 of 2



Special Markings:
Relay driver
Shelf Life:
N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200