## NSN 5963-01-080-4362

**Overall Length:** 

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-080-4362

| 2.620 inches                          |  |  |  |
|---------------------------------------|--|--|--|
| Overall Height:                       |  |  |  |
| 1.950 inches                          |  |  |  |
| Overall Width:                        |  |  |  |
| 0.290 inches                          |  |  |  |
| Environmental Protection:             |  |  |  |
| Salt spray resistant and vibration    |  |  |  |
| Operating Tempurature Range:          |  |  |  |
| +0.0/+60.0 degrees celsius            |  |  |  |
| Average Life Rating:                  |  |  |  |
| 500.0                                 |  |  |  |
| Storage Tempurature Range:            |  |  |  |
| -62.0/+125.0 degrees celsius          |  |  |  |
| Average Life Measurement:             |  |  |  |
| Hours                                 |  |  |  |
| Average Life Rating In Hours:         |  |  |  |
| 500.0                                 |  |  |  |
| Basic Shape Style:                    |  |  |  |
| Rectangular or square                 |  |  |  |
| Inclosure Type:                       |  |  |  |
| Encased                               |  |  |  |
| Operating Control Method:             |  |  |  |
| Automatic                             |  |  |  |
| Installation Design:                  |  |  |  |
| Module                                |  |  |  |
| Control Type:                         |  |  |  |
| Remote                                |  |  |  |
| Circuit Construction Type:            |  |  |  |
| Solid state                           |  |  |  |
| Signal Voltage Rating Per Channel:    |  |  |  |
| 800.000 millivolts interstage         |  |  |  |
| Signal Data Type Per Channel:         |  |  |  |
| 2nd input channel digital err-100     |  |  |  |
| Connection Type And Location:         |  |  |  |
| Connector, plug bottom                |  |  |  |
| Maximum Power Drain Rating:           |  |  |  |
| 1.0 watts                             |  |  |  |
| Connection Contact Type And Quantity: |  |  |  |
| 1 connector, plug external            |  |  |  |
| Special Features:                     |  |  |  |

Key code fqh

## NSN 5963-01-080-4362

Standardized Electronic Module - Page 2 of 2



| Speci | al IV | alnı | HUS. |
|-------|-------|------|------|
|       |       |      |      |

Shift register

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200