## NSN 5963-01-113-1922

Overall Length:

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-113-1922

2.620 inches
Overall Height:
1.950 inches
Overall Width:
0.290 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Rating:
500.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
500.0
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Lilodoca
Operating Control Method:
Operating Control Method:
Operating Control Method: Automatic
Operating Control Method: Automatic Installation Design:
Operating Control Method: Automatic Installation Design: Module
Operating Control Method: Automatic Installation Design: Module Control Type:
Operating Control Method: Automatic Installation Design: Module Control Type: Remote
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type:
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel:
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 500.000 millivolts interstage preset
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 500.000 millivolts interstage preset Signal Data Type Per Channel:
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 500.000 millivolts interstage preset Signal Data Type Per Channel: 2nd output channel digital err-100
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 500.000 millivolts interstage preset Signal Data Type Per Channel: 2nd output channel digital err-100 Connection Type And Location:
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 500.000 millivolts interstage preset Signal Data Type Per Channel: 2nd output channel digital err-100 Connection Type And Location: Connector, plug bottom
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 500.000 millivolts interstage preset Signal Data Type Per Channel: 2nd output channel digital err-100 Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating:
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 500.000 millivolts interstage preset Signal Data Type Per Channel: 2nd output channel digital err-100 Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 1155.0 milliwatts
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 500.000 millivolts interstage preset Signal Data Type Per Channel: 2nd output channel digital err-100 Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 1155.0 milliwatts Connection Contact Type And Quantity:
Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Voltage Rating Per Channel: 500.000 millivolts interstage preset Signal Data Type Per Channel: 2nd output channel digital err-100 Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 1155.0 milliwatts Connector, plug external

## NSN 5963-01-113-1922

Standardized Electronic Module - Page 2 of 2



Cognizant Service:
Usn
Special Markings:
Multiplexer, digital
Test Data Document:
81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Type/model Designation:
And
Specification Data:
81349-mil-m-28787/78 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A32200