

View Online at https://aerobasegroup.com/nsn/5963-01-122-8260

Overall Length:
2.620 inches
Overall Height:
1.950 inches
Overall Width:
0.290 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Rating:
500.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
500.0
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
10.0 kilohertz operating channel
Signal Voltage Rating Per Channel:
5.000 volts input
Signal Data Type Per Channel:
Operating channel radio frequency err-100
Connection Type And Location:
Connector, plug bottom
Connection Contact Type And Quantity:
1 connector, plug external
External Dc Operating Voltage In Volts:
-15.0 1st voltage err-100

Standardized Electronic Module - Page 2 of 2



Cognizant Service:

Usn

Special Markings:

Modulator, synchronous

Test Data Document:

81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Type/model Designation:

Kad

Specification Data:

81349-mil-m-28787/220 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200