## NSN 5963-01-129-7769

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-129-7769

| Overall Length:                         |
|---|
| 2.620 inches                            |
| Overall Height:                         |
| 1.950 inches                            |
| Overall Width:                          |
| 0.290 inches                            |
| Environmental Protection:               |
| Salt spray resistant and vibration      |
| Operating Tempurature Range:            |
| +0.0/+60.0 degrees celsius              |
| Average Life Rating:                    |
| 500.0                                   |
| Storage Tempurature Range:              |
| -62.0/+125.0 degrees celsius            |
| Average Life Measurement:               |
| Hours                                   |
| Average Life Rating In Hours:           |
| 500.0                                   |
| Basic Shape Style:                      |
| Rectangular or square                   |
| Inclosure Type:                         |
| Encased                                 |
| Operating Control Method:               |
| Automatic                               |
| Installation Design:                    |
| Module                                  |
| Control Type:                           |
| Remote                                  |
| Circuit Construction Type:              |
| Solid state                             |
| Average Power Rating Per Channel:       |
| 710.0 milliwatts output                 |
| Signal Voltage Rating Per Channel:      |
| 800.000 millivolts interstage           |
| Signal Data Type Per Channel:           |
| 2nd output channel digital err-100      |
| Connection Type And Location:           |
| Connector, plug bottom                  |
| Connection Contact Type And Quantity:   |
| 1 connector, plug external              |
| External Dc Operating Voltage In Volts: |
| -5.0. 1st voltage err-100               |

·5.0 1st voltage err-100

## NSN 5963-01-129-7769

Standardized Electronic Module - Page 2 of 2



| Cognizant Service:   |
|--|
| Usn  |
| Special Markings:  |
| Translate driver, digital  |
| Test Data Document:  |
| 81349-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental        |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  |
| Type/model Designation:  |
| Mdp  |
| Specification Data:  |
| 81349-mil-m-28787/48 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A32200   |
|  |