

NSN 5963-01-161-3404

Standardized Electronic Module - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5963-01-161-3404
Overall Length:
2.620 inches
Overall Height:
1.950 inches
Overall Width:
0.290 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Rating:
500.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
500.0
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
20.0 megahertz operating channel
Signal Voltage Rating Per Channel:
800.000 millivolts interstage
Signal Data Type Per Channel:
Operating channel radio frequency or 100

Operating channel radio frequency err-100

**Connection Type And Location:** 

Connector, plug bottom

**Maximum Power Drain Rating:** 

550.0 milliwatts

**Connection Contact Type And Quantity:** 

1 connector, plug external

## NSN 5963-01-161-3404

Standardized Electronic Module - Page 2 of 2



External Dc Operating Voltage In Volts:
5.0 single voltage
Cognizant Service:
Usn
Special Markings:
Gate, nand, digital
Test Data Document:
81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Type/model Designation:
Gda
Specification Data:
81349-mil-m-28787/3 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A32200