

NSN 5963-01-164-7409 Standardized Electronic Module - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5963-01-164-7409 **Overall Length:** 2.620 inches **Overall Height:** 1.950 inches **Overall Width:** 0.290 inches **Environmental Protection:** Salt spray resistant and vibration **Operating Tempurature Range:** +0.0/+60.0 degrees celsius **Average Life Rating:** 500.0 **Storage Tempurature Range:** -62.0/+125.0 degrees celsius **Average Life Measurement:** Hours **Average Life Rating In Hours:** 500.0 **Basic Shape Style:** Rectangular or square **Inclosure Type:** Encased **Operating Control Method:** Automatic **Installation Design:** Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

25.0 megahertz operating channel

Signal Voltage Rating Per Channel:

400.000 millivolts interstage preset

Signal Data Type Per Channel:

Operating channel radio frequency err-100

Connection Type And Location:

Connector, plug bottom

Maximum Power Drain Rating:

212.0 milliwatts

Connection Contact Type And Quantity:

1 connector, plug external

NSN 5963-01-164-7409

Standardized Electronic Module - Page 2 of 2



| External DC Operating Voltage in Volts: |
|--|
| 5.0 single voltage |
| Cognizant Service: |
| Usn |
| Special Markings: |
| Flip-flop, jk, digital |
| Test Data Document: |
| 81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Type/model Designation: |
| Ghk |
| Specification Data: |
| 81349-mil-m-28787/296 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A32200 |
| |