NSN 5963-01-166-3797

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-166-3797

Overall Length:

Between 2.930 inches and 3.010 inches

Overall Height:

Between 0.710 inches and 0.790 inches

Overall Width:

Between 1.900 inches and 1.980 inches

Environmental Protection:

Moisture proof and shock resistant and vibration

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Average Life Measurement:

Indefinite

Basic Shape Style:

Rectangular or square

Identification Designator:

154068p2-94117

Inclosure Type:

Encased

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

393.0 megahertz operating channel

Frequency Adjustment Type:

Continuous

Average Power Rating Per Channel:

31.6 milliwatts output

Impedance Rating Per Channel:

50.000 ohms operating channel

Connection Type And Location:

Receptacle, coaxial right side and printed circuit front

Connection Contact Type And Quantity:

1 receptacle, coaxial external and 5 printed circuit external

External Dc Operating Voltage In Volts:

14.25 single voltage and 15.75 single voltage

Special Features:

Sinewave output

NSN 5963-01-166-3797

Crystal Controlled Oscillator - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200