Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-178-4340

Ov	rerall Length:
2.6	320 inches
Ov	erall Height:
1.9)50 inches
Ov	erall Width:
0.5	i90 inches
Env	vironmental Protection:
Sal	It spray resistant and vibration
Ор	perating Tempurature Range:
+0.	.0/+60.0 degrees celsius
Ave	erage Life Rating:
500	0.0
Sto	prage Tempurature Range:
-62	2.0/+125.0 degrees celsius
Ave	erage Life Measurement:
Ho	urs
Ave	erage Life Rating In Hours:
500	0.0
Bas	sic Shape Style:
Ree	ctangular or square
Inc	closure Type:
End	cased
Ор	perating Control Method:
Aut	tomatic
Ins	stallation Design:
Мо	odule
Co	ontrol Type:
Rei	mote
Cir	rcuit Construction Type:
	lid state
-	gnal Voltage Rating Per Channel:
	0.000 millivolts input
-	gnal Data Type Per Channel:
	d input channel digital err-100
	nnection Type And Location:
	nnector, plug bottom
	iximum Power Drain Rating:
	0.0 milliwatts
	nnection Contact Type And Quantity:
	connector, plug external
	ternal Dc Operating Voltage In Volts:
5.0) single voltage

Standardized Electronic Module - Page 2 of 2



Cognizant Service:

Usn

Special Markings:

Encoder, fault isolation

Test Data Document:

81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Type/model Designation:

Mfg

Specification Data:

81349-mil-m-28787/344 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200