NSN 5963-01-216-0104

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-216-0104

| Overall Length: |
|---|
| 2.620 inches |
| Overall Height: |
| 1.950 inches |
| Overall Width: |
| 0.290 inches |
| Environmental Protection: |
| Salt spray resistant and vibration |
| Operating Tempurature Range: |
| +0.0/+60.0 degrees celsius |
| Average Life Rating: |
| 500.0 |
| Storage Tempurature Range: |
| -62.0/+125.0 degrees celsius |
| Average Life Measurement: |
| Hours |
| Average Life Rating In Hours: |
| 500.0 |
| Basic Shape Style: |
| Rectangular or square |
| Inclosure Type: |
| Encased |
| Operating Control Method: |
| Automatic |
| Installation Design: |
| Module |
| Control Type: |
| Remote |
| Circuit Construction Type: |
| Solid state |
| Signal Voltage Rating Per Channel: |
| 500.000 millivolts interstage preset |
| Signal Data Type Per Channel: |
| 2nd output channel digital err-100 |
| Connection Type And Location: |
| Connector, plug bottom |
| Maximum Power Drain Rating: |
| 2.0 watts |
| Connection Contact Type And Quantity: |
| 1 connector, plug external |
| External Dc Operating Voltage In Volts: |
| 5.000 single voltage |

NSN 5963-01-216-0104

Fiig: A32200

Standardized Electronic Module - Page 2 of 2



| Cognizant Service: |
|---|
| Jsn |
| Special Markings: |
| Memory, read only, digital |
| Test Data Document: |
| 21877-167898-103 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Гуре/model Designation: |
| Rom |
| Shelf Life: |
| N/a |
| Jnit Of Measure: |
| - |
| Demilitarization: |
| Yes - demil/mli |