

View Online at https://aerobasegroup.com/nsn/5963-01-222-0034

Overall Length:2.620 inchesOverall Height:1.950 inchesOverall Width:0.290 inchesEnvironmental Protection:Salt spray resistant and vibrationOperating Tempurature Range:+0.0 to 60.0 degrees celsiusStorage Tempurature Range:-62.0 to 125.0 degrees celsiusAverage Life Measurement:HoursBasic Shape Style:Rectangular or squareInclosure Type:EncasedOperating Control Method:AutomaticInstallation Design:ModuleCircuit Construction Type:Solid stateSignal Data Type Per Channel:Operating channel discrete voltageConnector, plug bettmalConnector, plug bottmalSolid stateSignal Data Type And Location:Connector, plug bottmalSol single voltageSpecial Markings:Standard, filterType/model Designation:LorSheff Life:NaVint Of Measure:	
Overall Height:1.950 inchesOverall Width:0.290 inchesEnvironmental Protection:Salt spray resistant and vibrationOperating Tempurature Range:+0.0 to 60.0 degrees celsiusStorage Tempurature Range:-62.0 to 125.0 degrees celsiusAverage Life Measurement:HoursBasic Shape Style:Rectangular or squareInclosure Type:EncasedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:Solid stateSignal Data Type Per Channel:Operating channel discrete voltageConnector, plug bottomConnector, plug bottomConnector, plug externalExternal Dc Operating Voltage In Volts:5.0 single voltageSpecial Markings:Standard, filterType/model Designation:LorSheff Life:Na	Overall Length:
1.950 inches 0.290 inches Environmental Protection: Salt spray resistant and vibration Operating Tempurature Range: +0.0 to 60.0 degrees celsius Storage Tempurature Range: -62.0 to 125.0 degrees celsius Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Signal Data Type Per Channel: Operating channel discrete voltage Connection, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lor Sheff Life: Na	2.620 inches
Overall Width:0.290 inchesEnvironmental Protection:Salt spray resistant and vibrationOperating Tempurature Range:+0.0 to 60.0 degrees celsiusStorage Tempurature Range:-62.0 to 125.0 degrees celsiusAverage Life Measurement:HoursBasic Shape Style:Rectangular or squareInclosure Type:EncasedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:Solid stateSignal Data Type Per Channel:Operating channel discrete voltageConnector, plug bottomConnector, plug bottomConnector, plug bottomSolid stateSignal Data Type And Quantity:1 connector, plug externalExternal Dc Operating Voltage In Volts:5.0 single voltageSpecial Markings:Standard, filterType/model Designation:LorShelf Life:Nya	Overall Height:
0.290 inches Environmental Protection: Salt spray resistant and vibration Operating Tempurature Range: +0.0 to 60.0 degrees celsius Storage Tempurature Range: -62.0 to 125.0 degrees celsius Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Gircuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connector, plug bottom Connec	1.950 inches
Environmental Protection: Salt spray resistant and vibration Operating Tempurature Range: +0.0 to 60.0 degrees celsius Storage Tempurature Range: -62.0 to 125.0 degrees celsius Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug bottom Sol single voltage Special Markings: Standard, filter Type/model Designation: Lor Shelf Life: N/a	Overall Width:
Salt spray resistant and vibration Operating Tempurature Range: +0.0 to 60.0 degrees celsius Storage Tempurature Range: -62.0 to 125.0 degrees celsius Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Gircuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: S.0 single voltage Special Markings: Standard, filter Type/model Designation: Lor N/a	0.290 inches
Note+0.0 to 60.0 degrees celsiusStorage Tempurature Range:-62.0 to 125.0 degrees celsiusAverage Life Measurement:HoursBasic Shape Style:Rectangular or squareInclosure Type:EncasedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:RemoteSignal Data Type Per Channel:Operating channel discrete voltageConnector, plug bottomConnector, plug bottomConnector, plug externalExternal Dc Operating Voltage In Volts:5.0 single voltageSpecial Markings:Standard, filterType/model Designation:LorShelf Life:N/a	Environmental Protection:
+0.0 to 60.0 degrees celsius Storage Tempurature Range: -62.0 to 125.0 degrees celsius Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr N/a	Salt spray resistant and vibration
Storage Tempurature Range:-62.0 to 125.0 degrees celsiusAverage Life Measurement:HoursBasic Shape Style:Rectangular or squareInclosure Type:EncasedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:RemoteCircuit Construction Type:Solid stateSignal Data Type Per Channel:Operating channel discrete voltageConnection, plug bottomConnector, plug bottomSolo single voltageSpecial Markings:Standard, filterType/model Designation:LorShelf Life:N/a	Operating Tempurature Range:
 -62.0 to 125.0 degrees celsius Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Solid state Special Markings: Standard, filter Type/model Designation: Lor Shelf Life: N/a 	+0.0 to 60.0 degrees celsius
Average Life Measurement:HoursBasic Shape Style:Rectangular or squareInclosure Type:EncasedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:RemoteCircuit Construction Type:Solid stateSignal Data Type Per Channel:Operating channel discrete voltageConnection Type And Location:Connector, plug bottomConnector, plug bottomSolid stateSingle voltageSpecial Markings:Standard, filterType/model Designation:LorShelf Life:N/a	Storage Tempurature Range:
Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Signal Data Type And Location: Connector, plug bottom Solo single voltage Special Markings: Standard, filter Type/model Designation: Lcr N/a	-62.0 to 125.0 degrees celsius
Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Average Life Measurement:
Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: S.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr N/a	Hours
Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life:	Basic Shape Style:
Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: Sol single voltage Special Markings: Lar Standard, filter Lic Shelf Life: N/a	Rectangular or square
Operating Control Method:AutomaticInstallation Design:ModuleControl Type:RemoteCircuit Construction Type:Solid stateSignal Data Type Per Channel:Operating channel discrete voltageConnection Type And Location:Connector, plug bottomConnector, plug bottomConnector, plug bottomSolid stageSpecial Markings:Standard, filterType/model Designation:LcrShelf Life:N/a	Inclosure Type:
Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Encased
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lor Shelf Life: N/a	Operating Control Method:
Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: S.0 single voltage Special Markings: Standard, filter Lor Shelf Life: N/a	Automatic
Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lor Shelf Life: N/a	Installation Design:
Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Lor Shelf Life: N/a	Module
Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Control Type:
Solid state Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Remote
Signal Data Type Per Channel: Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external 1 connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Circuit Construction Type:
Operating channel discrete voltage Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Solid state
Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Signal Data Type Per Channel:
Connector, plug bottom Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Operating channel discrete voltage
Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Connection Type And Location:
1 connector, plug external External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Connector, plug bottom
External Dc Operating Voltage In Volts: 5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	Connection Contact Type And Quantity:
5.0 single voltage Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	1 connector, plug external
Special Markings: Standard, filter Type/model Designation: Lcr Shelf Life: N/a	External Dc Operating Voltage In Volts:
Standard, filter Type/model Designation: Lcr Shelf Life: N/a	5.0 single voltage
Type/model Designation: Lcr Shelf Life: N/a	Special Markings:
Lcr Shelf Life: N/a	Standard, filter
Shelf Life: N/a	Type/model Designation:
N/a	Lcr
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:



Demilitarization:

Yes - demil/mli

Fiig:

A32200