Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-229-9376

Overall Length:
2.620 inches
Overall Height:
1.950 inches
Overall Width:
0.290 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0 to 60.0 degrees celsius
Storage Tempurature Range:
-62.0 to 125.0 degrees celsius
Average Life Measurement:
Hours
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Module Control Type:
Control Type:
Control Type: Remote
Control Type: Remote Circuit Construction Type:
Control Type: Remote Circuit Construction Type: Solid state
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location:
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating:
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 2.9 watts
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 2.9 watts Connection Contact Type And Quantity:
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 2.9 watts Connection Contact Type And Quantity: 1 connector, plug external
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 2.9 watts Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts:
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 2.9 watts Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.5 single voltage
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 2.9 watts Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.5 single voltage Special Features:
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 2.9 watts Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.5 single voltage Special Features: Key code w3z
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 2.9 watts Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.5 single voltage Special Features: Key code w3z Special Markings:
Control Type: Remote Circuit Construction Type: Solid state Connection Type And Location: Connector, plug bottom Maximum Power Drain Rating: 2.9 watts Connection Contact Type And Quantity: 1 connector, plug external External Dc Operating Voltage In Volts: 5.5 single voltage Special Features: Key code w3z Special Markings: Rom/prom

--



Demilitarization:

Yes - demil/mli

Fiig:

A32200