

View Online at https://aerobasegroup.com/nsn/5963-01-254-9281

| C | Overall Length: |
|---|--|
| 2 | 2.620 inches |
| C | Overall Height: |
| 1 | .950 inches |
| C | Overall Width: |
| С | 0.290 inches |
| E | Environmental Protection: |
| 5 | Salt spray resistant and vibration |
| C | Operating Tempurature Range: |
| + | -0.0/+60.0 degrees celsius |
| A | Average Life Rating: |
| 5 | 500.0 |
| 5 | Storage Tempurature Range: |
| - | 62.0/+125.0 degrees celsius |
| A | Average Life Measurement: |
| ŀ | lours |
| A | Average Life Rating In Hours: |
| 5 | 500.0 |
| E | Basic Shape Style: |
| F | Rectangular or square |
| l | nclosure Type: |
| E | Encased |
| C | Operating Control Method: |
| A | Automatic |
| l | nstallation Design: |
| Ν | <i>A</i> odule |
| C | Control Type: |
| F | Remote |
| C | Circuit Construction Type: |
| S | Solid state |
| 5 | Signal Voltage Rating Per Channel: |
| 5 | 500.000 millivolts interstage preset |
| 5 | Signal Data Type Per Channel: |
| 4 | Ith input channel digital err-100 |
| C | Connection Type And Location: |
| C | Connector, plug bottom |
| C | Connection Contact Type And Quantity: |
| 1 | connector, plug external |
| E | External Dc Operating Voltage In Volts: |
| 3 | 8.0 single voltage and 18.0 single voltage |
| C | Cognizant Service: |
| | len |

Usn

Standardized Electronic Module - Page 2 of 2



Special Markings:

Counter, binary/bcd

Test Data Document:

81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Type/model Designation:

Bmg

Specification Data:

81349-mil-m-28787/275 government specification

Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A32200