Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-263-1444

| Overall Length:  |
|--|
| 2.620 inches   |
| Overall Height:  |
| 0.290 inches   |
| Overall Width:   |
| 1.950 inches   |
| Environmental Protection:  |
| Salt spray resistant and vibration                               |
| Operating Tempurature Range:                                     |
| +0.0/+60.0 degrees celsius                                       |
| Storage Tempurature Range:                                       |
| -62.0/+125.0 degrees celsius                                     |
| Average Life Measurement:  |
| Indefinite   |
| Basic Shape Style:   |
| Rectangular or square  |
| Inclosure Type:  |
| Encased  |
| Operating Control Method:  |
| Automatic  |
| Installation Design:   |
| Module   |
| Control Type:  |
| Remote   |
| Circuit Construction Type:                                       |
| Solid state  |
| Signal Data Type Per Channel:                                    |
| Operating channel digital  |
| Connection Type And Location:                                    |
| Connector, plug bottom   |
| Connection Contact Type And Quantity:                            |
| 1 connector, plug external                                       |
| Special Features:  |
| Key code emk   |
| Special Markings:  |
| Gate, nand   |
| Test Data Document:  |
| 81349-mil-m-28787 specification (includes engineering type bulle |

81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-m-28787/260 government specification

Shelf Life:

N/a

Standardized Electronic Module - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32200