Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-274-9436

| Overall Length: | | | |
|-------------------------------|------------------|--|--|
| 5.620 inches | | | |
| Overall Height: | | | |
| 1.950 inches | | | |
| Overall Width: | | | |
| 0.290 inches | | | |
| Environmental Protection | on: | | |
| Salt spray resistant and v | ibration | | |
| Operating Tempurature | Range: | | |
| +0.0/+60.0 degrees celsion | s | | |
| Average Life Rating: | | | |
| 500.0 | | | |
| Storage Tempurature R | ange: | | |
| -62.0/+125.0 degrees cel | sius | | |
| Average Life Measurem | ent: | | |
| Hours | | | |
| Average Life Rating In I | lours: | | |
| 500.0 | | | |
| Basic Shape Style: | | | |
| Rectangular or square | | | |
| Inclosure Type: | | | |
| Encased | | | |
| Operating Control Meth | od: | | |
| Automatic | | | |
| Installation Design: | | | |
| Module | | | |
| Control Type: | | | |
| Remote | | | |
| Circuit Construction Ty | pe: | | |
| Solid state | | | |
| Signal Voltage Rating P | | | |
| 500.000 millivolts intersta | | | |
| Signal Data Type Per Cl | | | |
| 1st output channel digital | | | |
| Connection Type And L | ocation: | | |
| Connector, plug bottom | | | |
| Connection Contact Ty | | | |
| 1 connector, plug externa | | | |
| External Dc Operating \ | oltage In Volts: | | |
| 5.5 single voltage | | | |
| Cognizant Service: | | | |
| Usn | | | |



Special Markings:

Memory, read only

Type/model Designation:

Vnaw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200