Standardized Electronic Module - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5963-01-294-6715

Overall Length:2.620 inchesOverall Height:1.950 inchesOverall Width:0.290 inchesEnvironmental Protection:Salt spray resistant and vibrationAverage Life Measurement:HoursBasic Shape Style:Rectangular or squareInclosure Type:EncasedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:Solid stateSignal Data Type Per Channel:Operating channel digitalConnection Type And Location:Connector, plug bottomConnector, plug bottomConnector, plug bottomSpecial Features:Key code cxmSpecial Markings:Pulse driverInt of Measure:Pure trip:AutomaticPure trip:Solid StateSpecial Markings:Pulse driverStelf Life:N/aUnit Of Measure:Solid StateSpecial MarkingsSpecial MarkingsPulse driverShelf Life:N/aUnit Of Measure:Special MarkingsAutomaticPornelitarization:-Special Markings-Special MarkingsSpecial Markings <td< th=""><th></th><th></th></td<>		
Overall Height:         1.950 inches         Overall Width:         0.290 inches         Environmental Protection:         Salt spray resistant and vibration         Average Life Measurement:         Hours         Basic Shape Style:         Rectangular or square         Inclosure Type:         Encased         Operating Control Method:         Automatic         Installation Design:         Module         Control Type:         Remote         Signal Data Type Per Channel:         Operating channel digital         Connection, plug bottom         Connector, plug bottom         Special Features:         Key code cxm         Special Markings:         Pulse driver         Sheft Life:         N/a         Unit Of Measure:         -         Demilitarization:         Yes - demil/mli	0	Overall Length:
1.950 inches Overall Width: 0.290 inches Environmental Protection: Salt spray resistant and vibration Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Signal Data Type Per Channel: Operating channel digital Connector, plug bottom Connector, plug bottom Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure: Commention Superation Sup		2.620 inches
Overall Width:0.290 inchesEnvironmental Protection:Salt spray resistant and vibrationAverage Life Measurement:HoursBasic Shape Style:Rectangular or squareInclosure Type:EncasedOperating Control Method:AutomaticInstallation Design:ModuleControl Type:Solid stateSignal Data Type Per Channel:Operating channel digitalConnector, plug bottomConnector, plug externalSpecial Features:Key code cxmSpecial Markings:Pulse driverShelf Life:N/aUnit Of Measure:-Demilitarization:Yes - demi//mliFig:	(	Overall Height:
0.290 inches Environmental Protection: Salt spray resistant and vibration Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connector, plug bottom Connector, plug bottom Special Features: Key code cxm Special Methigs: Pulse driver Shelf Life: N/a Unit of Measure: Commiltarization: Yes - demil/mli Fig:		1.950 inches
Environmental Protection: Salt spray resistant and vibration Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Temilitarization: Yes - demil/mli Filg:		Overall Width:
Salt spray resistant and vibration Average Life Measurement: Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Gircuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connector, plug bottom Connector, plug bottom Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: Na	(	0.290 inches
Average Life Measurement:         Hours         Basic Shape Style:         Rectangular or square         Inclosure Type:         Encased         Operating Control Method:         Automatic         Installation Design:         Module         Control Type:         Remote         Gircuit Construction Type:         Solid state         Signal Data Type Per Channel:         Operating channel digital         Connection, Jupe And Location:         Connector, plug bottom         Connector, plug external         Special Features:         Key code cxm         Special Markings:         Pulse driver         Sheff Life:         N/a         Unit Of Measure:         -         Featilitarization:         Yes - demil/mli	l	Environmental Protection:
Hours Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure: T Fig:		Salt spray resistant and vibration
Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:		Average Life Measurement:
Rectangular or square Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connector, plug Per Channel: Connector, plug bottom Connector, plug bottom Sopecial Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	l	Hours
Inclosure Type: Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug bottom Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli	I	Basic Shape Style:
Encased Operating Control Method: Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug bottom Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli	l	Rectangular or square
Operating Control Method:   Automatic   Installation Design:   Module   Control Type:   Remote   Circuit Construction Type:   Solid state   Signal Data Type Per Channel:   Operating channel digital   Connection Type And Location:   Connector, plug bottom   Connector, plug bottom   Connector, plug external   Special Features:   Key code cxm   Sheff Life:   N/a   Unit Of Measure:   -   Persilitarization:   Yes - demil/mli   Fiig:	I	Inclosure Type:
Automatic Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	I	Encased
Installation Design: Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Temilitarization: Yes - demil/mli Fiig:	(	Operating Control Method:
Module Control Type: Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:		Automatic
Control Type:   Remote   Circuit Construction Type:   Solid state   Signal Data Type Per Channel:   Operating channel digital   Connection Type And Location:   Connector, plug bottom   Connector, plug bottom   Connector, plug bottom   Special Features:   Key code cxm   Special Markings:   Pulse driver   Shelf Life:   N/a   Unit Of Measure:     Yes - demil/mli   Fig:	I	Installation Design:
Remote Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	I	Module
Circuit Construction Type: Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug bottom Connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli	0	Control Type:
Solid state Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure: Fer Yes - demil/mli Fig:	I	Remote
Signal Data Type Per Channel: Operating channel digital Connection Type And Location: Connector, plug bottom Connector, plug bottom Connector, plug external Special Centures: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Fusial Centure Fig:	(	Circuit Construction Type:
Operating channel digital Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity: 1 connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	;	Solid state
Connection Type And Location: Connector, plug bottom Connection Contact Type And Quantity: 1 connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Fig:	;	Signal Data Type Per Channel:
Connector, plug bottom Connection Contact Type And Quantity: 1 connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Fig:	(	Operating channel digital
Connection Contact Type And Quantity: 1 connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	(	Connection Type And Location:
1 connector, plug external Special Features: Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Femilitarization: Yes - demil/mli Fig:	(	Connector, plug bottom
Special Features:   Key code cxm   Special Markings:   Pulse driver   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   Yes - demil/mli   Fig:	(	Connection Contact Type And Quantity:
Key code cxm Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:		1 connector, plug external
Special Markings: Pulse driver Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	;	Special Features:
Pulse driver Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	I	Key code cxm
Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	;	Special Markings:
N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	l	Pulse driver
Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	;	Shelf Life:
 Demilitarization: Yes - demil/mli Fiig:	I	N/a
Yes - demil/mli Fiig:	I	Unit Of Measure:
Yes - demil/mli Fiig:		-
Fiig:	I	Demilitarization:
-		Yes - demil/mli
A32200	l	Filg:
		A32200