## NSN 5963-01-331-3962

Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-331-3962

Overall Length:
2.620 inches
Overall Height:
1.950 inches
Overall Width:
0.290 inches
Environmental Protection:
Salt spray resistant and vibration
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Average Life Rating:
500.0
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
500.0
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Signal Voltage Rating Per Channel:
400.000 millivolts interstage preset
Signal Data Type Per Channel:
2nd output channel digital err-100
Connection Type And Location:
Connector, plug bottom
Connector, plug bottom  Maximum Power Drain Rating:
Maximum Power Drain Rating:
Maximum Power Drain Rating:  1.3 watts
Maximum Power Drain Rating:  1.3 watts  Connection Contact Type And Quantity:

## NSN 5963-01-331-3962

Yes - demil/mli

**Fiig:** A32200

Standardized Electronic Module - Page 2 of 2



Special Features:
Key code kdn
Special Markings:
Receiver, differential line
Test Data Document:
81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-28787/53 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: