Standardized Electronic Module - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5963-01-349-3343

view Online at https://aeiobasegioup.com/nsn/3903-01-343-3343	
Overall Length:	
5.740 inches	
Overall Height:	
0.290 inches	
Overall Width:	
1.950 inches	
Environmental Protection:	
Salt spray resistant and vibration	
Operating Tempurature Range:	
+0.0/+60.0 degrees celsius	
Average Life Rating:	
500.0	
Storage Tempurature Range:	
-62.0/+125.0 degrees celsius	
Average Life Measurement:	
Hours	
Average Life Rating In Hours:	
500.0	
Basic Shape Style:	
Rectangular or square	
Inclosure Type:	
Encased	
Operating Control Method:	
Automatic	
Installation Design:	
Module	
Control Type:	
Remote	
Circuit Construction Type:	
Solid state	
Signal Voltage Rating Per Channel:	
500.000 millivolts interstage preset2.400 volts input preset and 4.500 volts interstage preset	
Signal Data Type Per Channel:	
1st output channel digital err-100 2nd output channel digital err-100	
Connection Type And Location:	
Connector, plug bottom	
Connection Contact Type And Quantity:	
1 connector, plug external	
External Dc Operating Voltage In Volts:	
5.5 single voltage	
Special Features:	
Key code cem	

Standardized Electronic Module - Page 2 of 2



## **Special Markings:**

Controller/timing module

## **Test Data Document:**

81349-mil-m-28787 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-m-28787/363 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32200