

View Online at <https://aerobasegroup.com/nsn/5963-01-525-4924>

Shock Resistance Rating In Gravitational Units:

50.0

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Average Life Rating:

30000.0

Average Life Measurement:

Hours

End Application:

Nato seasparrow surface missile system

Basic Shape Style:

Irregular

Maximum Operating Altitude Rating:

8000.0 feet

Inclosure Type:

Hermetically sealed

Installation Design:

Module

Circuit Construction Type:

Solid state

Frequency Per Channel:

Not rated

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

Not rated

Impedance Rating Per Channel:

Not rated

Pulse Peak Amplitude Per Channel:

Not rated

Shock Pulse Duration Time:

11.0 milliseconds

External Dc Operating Voltage In Volts:

0.25 1st voltage err-100 and 7.6 1st voltage err-100

Product Name:

Module, power amplifier

Special Features:

Warning, this part contains beryllium oxide

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200