

View Online at <https://aerobasegroup.com/nsn/5963-01-525-4924>

**Shock Resistance Rating In Gravitational Units:**

50.0

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Average Life Rating:**

30000.0

**Average Life Measurement:**

Hours

**End Application:**

Nato seasparrow surface missile system

**Basic Shape Style:**

Irregular

**Maximum Operating Altitude Rating:**

8000.0 feet

**Inclosure Type:**

Hermetically sealed

**Installation Design:**

Module

**Circuit Construction Type:**

Solid state

**Frequency Per Channel:**

Not rated

**Attenuation In Decibels:**

Not rated

**Average Power Rating Per Channel:**

Not rated

**Signal Voltage Rating Per Channel:**

Not rated

**Overall Gain:**

Not rated

**Impedance Rating Per Channel:**

Not rated

**Pulse Peak Amplitude Per Channel:**

Not rated

**Shock Pulse Duration Time:**

11.0 milliseconds

**External Dc Operating Voltage In Volts:**

0.25 1st voltage err-100 and 7.6 1st voltage err-100

**Product Name:**

Module, power amplifier

**Special Features:**

Warning, this part contains beryllium oxide

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32200