NSN 5965-00-011-6742

Dynamic Microphone - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5965-00-011-6742 **Body Style:** Mask type Width: 1.125 inches Length: 24.125 inches **Connector Manufacturer Code:** 96906 **Accessory Components:** Connector Frequency Response Range In Hertz: +300.0 to 4000.0 **Impedance Selection Method:** Screw type lead positioning Impedance Rating: 10.0 ohms **Output Sensitivity Rating In Decibels:** 35.0 **Output Sensitivity Rating Reference:** 0.0002 dynes per sq centimeter **Polarity Connection:** Not required **Sound Pickup Directional Type:** Bidirectional **Noise Canceling Feature:** Not included **Support Stand:** Not included **Shock Mount:** Not provided **Electrical Connection Type:** Integral cord **Connector Identification:** U173u **Extended Cable Length:** 2.0 preset inches **Cable Conductor Quantity:** 2 **Cable Shielded Conductor Quantity:**

Test Data Document:

81349-mil-m-21734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5965-00-011-6742

Dynamic Microphone - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A06400