## NSN 5965-00-011-6742

Dynamic Microphone - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5965-00-011-6742

Dedu Stude
Body Style:
Mask type
Width:
1.125 inches
Length:
24.125 inches
Connector Manufacturer Code:
96906
Accessory Components:
Connector
Frequency Response Range In Hertz:
+300.0 to 4000.0
Impedance Selection Method:
Screw type lead positioning
Impedance Rating:
10.0 ohms
Output Sensitivity Rating In Decibels:
35.0
Output Sensitivity Rating Reference:
0.0002 dynes per sq centimeter
Polarity Connection:
Not required
Sound Pickup Directional Type:
Bidirectional
Noise Canceling Feature:
Not included
Support Stand:
Not included
Shock Mount:
Not provided
Electrical Connection Type:
Integral cord
Connector Identification:
U173u
Extended Cable Length:
2.0 preset inches
Cable Conductor Quantity:
2
Cable Shielded Conductor Quantity:
2
Test Data Document:
01240 mil m 21724 encettion (includes encineering type byllating h

81349-mil-m-21734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5965-00-011-6742

Dynamic Microphone - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A06400

