NSN 5965-00-179-7762

Dynamic Microphone - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5965-00-179-7762

Body Style:
Hand held
Width:
2.500 inches
Length:
4.594 inches
Mounting Method:
Clip
Switch Type:
Push
Accessory Components:
Cable
Frequency Response Range In Hertz:
+300.0 to 3500.0
Impedance Rating:
150.0 ohms
Output Sensitivity Rating In Decibels:
-125.0
Output Sensitivity Rating Reference:
10 dynes per sq centimeter
Operating Dc Voltage In Volts:
24.0
Polarity Connection:
Not required
Sound Pickup Directional Type:
Semidirectional
Noise Canceling Feature:
Not included
Support Stand:
Not included
Shock Mount:
Not provided
Electrical Connection Type:
Integral cord
Extended Cable Length:
7.0 feet
Retracted Cable Length:
2.5 feet
Cable Conductor Quantity:
4
Operating Dc:
500.0 milliomporos

500.0 milliamperes

NSN 5965-00-179-7762

Dynamic Microphone - Page 2 of 2



Special Features:

Hand held microphone includes switch assembly, cable connector, hanger, and clothing clip; designed to be water resistant; used with military radios and public address systems

Height:

1.031 inches

Test Data Document:

81349-mil-e-55119 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-80d/u government specification

Fsc Application Data:

Heassets, handsets, microphones and speakers

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A06400