NSN 5965-00-295-8965

Dynamic Microphone - Page 1 of 2

Body Style:

Stand type w/ or w/o stand



View Online at https://aerobasegroup.com/nsn/5965-00-295-8965

Mounting Facility Thread Size:
5/8-27 npt
Diameter:
3.000 inches
Length:
3.000 inches
Mounting Method:
Threaded bushing
Switch Type:
Push
Connector Manufacturer Code:
98825
Accessory Components:
Connector
Frequency Response Range In Hertz:
+150.0 to 4500.0
Impedance Rating:
150.0 ohms
Output Sensitivity Rating In Decibels:
-64.0
Output Sensitivity Rating Reference:
10 dynes per sq centimeter
Polarity Connection:
Not required
Sound Pickup Directional Type:
Omnidirectional
Noise Canceling Feature:
Not included
Support Stand:
Not included
Shock Mount:
Not provided
Electrical Connection Type:
Integral cable
Connector Identification:
XI-3-11
Extended Cable Length:
15.0 feet
Cable Conductor Quantity:

NSN 5965-00-295-8965

Dynamic Microphone - Page 2 of 2



Cable Shielded Conductor Quantity:
1
Height:
4.000 inches
Test Data Document:
81349-mil-m-1101 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A06400