## NSN 5965-00-798-0318

Headset-microphone - Page 1 of 2

Frequency Rating:



View Online at https://aerobasegroup.com/nsn/5965-00-798-0318

| Between 0.3 kilohertz and 4.0 kilohertz      |
|--|
| Switch:                                      |
| Included                                     |
| Impedance Rating:                            |
| 100.0 ohms                                   |
| Earphone Element Type:                       |
| Dynamic                                      |
| Earphone Quantity:                           |
| 2  |
| Controlling Agency:                          |
| Jetds  |
| Identifying Number:                          |
| -6a/ur type no.                              |
| Operating Current Rating:                    |
| 50.0 milliamperes                            |
| Earphone Impedance Rating:                   |
| 600.0 ohms                                   |
| Earphone Controlling Agency:                 |
| Jetds  |
| Earphone Identifying Number:                 |
| H87au fsn 5965006650527 type no.             |
| Microphone Element Type:                     |
| Carbon                                       |
| Output Level Rating:                         |
| 17 db below 6 mw                             |
| Earphone Mounting Method:                    |
| Suspended on headband                        |
| Microphone Mounting Facility:                |
| Bracket fastened to headband                 |
| Connector Name:                              |
| Plug or plug                                 |
| Connector Identifying Number:                |
| +3292 part no. And pj054pmodified type no.   |
| Connector To Junction Cord Length:           |
| 2.375 feet                                   |
| Fsc Application Data:                        |
| Headsets, handsets, microphones and speakers |
| Shelf Life:                                  |
| N/a  |
| Unit Of Measure:                             |

--

## NSN 5965-00-798-0318

Headset-microphone - Page 2 of 2



Demilitarization:

No

Fiig:

T332-b