NSN 5965-00-946-1960

Dynamic Microphone - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5965-00-946-1960 **Body Style:** Stand type w/ or w/o stand **Mounting Facility Thread Size:** 5/8-27 npt Width: 2.188 inches Length: 7.375 inches **Mounting Method:** Threaded bushing Switch Type: Slide **Connector Manufacturer Code:** 71298 **Accessory Components:** Connector Frequency Response Range In Hertz: +50.0/+15000.0 **Impedance Selection Method:** Integral switch Impedance Rating: Between 35.0 ohms and 50.0 ohms and 150.0 ohms and 250.0 ohms and 35.0 kilohms **Output Sensitivity Rating In Decibels:** -55.5 and -55.5 and -56.6 and -55.5 **Output Sensitivity Rating Reference:** 1 milliwatt per 10 microbars and 1 milliwatt per 10 microbars and 1 volt per microbar and 1 volt per microbar and 1 volt per microbar **Polarity Connection:** Not required **Sound Pickup Directional Type:** Unidirectional **Noise Canceling Feature:** Not included **Support Stand:** Included **Shock Mount:** Not provided **Electrical Connection Type:**

Connector Identification: Mc3m

Integral cable

Extended Cable Length:

15.0 feet

NSN 5965-00-946-1960

Dynamic Microphone - Page 2 of 2



Cable Conductor Quantity:
2
Cable Shielded Conductor Quantity:
1
Height:
3.063 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A06400