

View Online at <https://aerobasegroup.com/nsn/5965-01-058-9785>

Terminal Quantity:

2

Terminal Type:

Tab, solder lug

Overall Depth:

2.000 inches

Overall Length:

Between 2.990 inches and 3.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches

Overall Width:

Between 2.990 inches and 3.010 inches

Mounting Hole Diameter:

Between 0.175 inches and 0.185 inches

Frequency Response Range In Hertz:

+400.0/+6000.0

Power Rating:

2.00 watts normal and 4.00 watts peak

Transducer Diameter:

1.500 inches

Mounting Facility Quantity:

4

Transducer Type:

Cone

Usage Design:

Indoor

Installation Design:

Nonportable

Impedance Rating In Ohms:

Between 7.0 voice coil and 9.0 voice coil

Mounting Method:

Unthreaded hole

Special Features:

This is unenclosed loudspeaker for 2 watt normal and 4 watt peak input. It has an 8 ohm impedance rating. This item is fungus, blast, and water resisting

Style Designator:

Square

Test Data Document:

81349-mil-I-12606 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Fsc Application Data:

Headsets, handsets, microphones and speakers

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A11600