

View Online at <https://aerobasegroup.com/nsn/5965-01-058-9785>

**Terminal Quantity:**

2

**Terminal Type:**

Tab, solder lug

**Overall Depth:**

2.000 inches

**Overall Length:**

Between 2.990 inches and 3.010 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.375 inches

**Overall Width:**

Between 2.990 inches and 3.010 inches

**Mounting Hole Diameter:**

Between 0.175 inches and 0.185 inches

**Frequency Response Range In Hertz:**

+400.0/+6000.0

**Power Rating:**

2.00 watts normal and 4.00 watts peak

**Transducer Diameter:**

1.500 inches

**Mounting Facility Quantity:**

4

**Transducer Type:**

Cone

**Usage Design:**

Indoor

**Installation Design:**

Nonportable

**Impedance Rating In Ohms:**

Between 7.0 voice coil and 9.0 voice coil

**Mounting Method:**

Unthreaded hole

**Special Features:**

This is unenclosed loudspeaker for 2 watt normal and 4 watt peak input. It has an 8 ohm impedance rating. This item is fungus, blast, and water resisting

**Style Designator:**

Square

**Test Data Document:**

81349-mil-I-12606 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Fsc Application Data:**

Headsets, handsets, microphones and speakers

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A11600