Permanent Magnet Loudspeaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5965-01-243-5494

Terminal Quantity:
2
Z Terminal Type:
Tab, solder lug
Overall Depth:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 6.178 inches and 6.218 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 6.178 inches and 6.218 inches
Overall Width:
Between 6.042 inches and 6.082 inches
Overall Diameter:
Between 6.605 inches and 6.645 inches
Frequency Response Tolerance In Decibels:
-5.0/+5.0
Frequency Response Range In Hertz:
+95.0/+7000.0
Power Rating:
9.00 watts peak
Mounting Facility Quantity:
4
Transducer Type:
Cone
Usage Design:
Indoor and outdoor
Installation Design:
Nonportable
Impedance Rating In Ohms:
Between 6.8 voice coil and 9.2 voice coil
Mounting Method:
Slot
Style Designator:
Round
Fsc Application Data:
Loudspeakers and loudspeaker microphone
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

No

NSN 5965-01-243-5494

Permanent Magnet Loudspeaker - Page 2 of 2

Fiig: A11600

