Permanent Magnet Loudspeaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5965-01-274-6488

Terminal Quantity:
2
Terminal Type:
Quick disconnect, male
Overall Depth:
Between 2.480 inches and 2.520 inches
Overall Length:
Between 4.040 inches and 4.080 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 3.307 inches and 3.317 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 3.307 inches and 3.317 inches
Overall Width:
Between 4.040 inches and 4.080 inches
Mounting Hole Diameter:
0.199 inches
Frequency Response Tolerance In Decibels:
-15.0/+15.0
Frequency Response Range In Hertz:
+300.0/+7000.0
Power Rating:
2.00 watts normal
Transducer Length:
Between 3.433 inches and 3.443 inches
Transducer Width:
1.812 inches
Mounting Facility Quantity:
4
Transducer Type:
Diaphragm
Usage Design:
Outdoor
Installation Design:
Nonportable
Impedance Rating In Ohms:
Between 7.0 voice coil and 9.0 voice coil
Mounting Method:
Unthreaded hole
Style Designator:
Square
Test Data Document:
80063-12606 specification (includes engineering type bulletins, brochures, etc., that ref

80063-12606 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).



Fsc Application Data:

Communications equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A11600