

View Online at <https://aerobasegroup.com/nsn/5965-01-413-7290>

Body Style:

Hand held

Width:

2.250 inches

Length:

3.563 inches

Mounting Method:

Clip

Case Material:

Plastic

Switch Type:

Push

Connector Manufacturer Code:

81349

Accessory Components:

Cable and connector

Unpackaged Unit Weight:

0.75 pounds

Specific Use:

Marine, underwater

Frequency Response Range In Hertz:

+300.0/+4000.0

Impedance Rating:

Between 80.0 ohms and 120.0 ohms

Output Sensitivity Rating In Decibels:

54.0

Output Sensitivity Rating Reference:

0.0002 dynes per sq centimeter

Operating Dc Voltage In Volts:

27.5

End Application:

Underwater special surveillance system, martin marietta corp, type an/bsy- (v) s

Polarity Connection:

Required

Sound Pickup Directional Type:

Unidirectional

Noise Canceling Feature:

Included

Support Stand:

Not included

Shock Mount:

Not provided

Electrical Connection Type:

Integral cable

Connector Identification:

Mil-c-55116/1

Cable Conductor Quantity:

4

Cable Shielded Conductor Quantity:

4

Operating Dc:

Between 7.0 milliamperes and 10.0 milliamperes

Special Features:

Does not include an amplifier

Functional Description:

Converts speech signals into electrical signals

Height:

1.563 inches

Test Data Document:

81349-mil-m-21393 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A06400

Mil-std (military Standard):

Mil-c-55116 spec.