

View Online at <https://aerobasegroup.com/nsn/5965-01-600-7864>

Overall Length:

5.2 inches

Overall Height:

4.2 inches

Overall Diameter:

5.2 inches

Mounting Configuration:

Threaded m6

Unpackaged Unit Weight:

5.4 pounds

Normal Input Wattage Rating In Watts:

200.0

Special Features:

40-00002-01 conquest loudspeaker driver (tcr900022-01) is a compression driver that produces 117db at 1 watt of power measures at 1 meter. impedance is 8 ohms. Dc resistance is 4.6 ohms. Frequency range is 300-6, 500 hzpower handling, ase standard is 90 watts. Peak power, 50ms is > 300 watts (no clipping allowed). Recommended amplifier input is 50-200 watts. High pass filter of 300 hz or higher, 18db/octave. Mounting is 4 holes at 90 degrees. Voice coil replacement is via 3 mm hex (allen) drive screws on rear of driver. Connection via spring-loaded nickel-plated hard brass terminals. Environmental: storage temp -55 to + 85 c. Operating temp -40 to +70 c. Humidity - any. Rain, horizontally mounted horn - ok. Salt spray - ok. Black in color. P/o ngl-s-d and ngl-s- m audio assembly

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T332-a