NSN 5970-00-025-7939

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-025-7939

Reliability Indicator: Not established **Tempurature Rating:** -55.0 degrees celsius and 225.0 degrees celsius **Environmental Protection:** Corrosion resistant and mildew resistant and water resistant Large End Wall Thickness Of Main Body: 0.050 inches as supplied Small End Wall Thickness Of Main Body: 0.050 inches after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 0.650 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.920 inches as supplied Main Body Large End Inside Diameter: 0.920 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: 0.280 inches after unrestricted recovery Angle Between Large End And Small End Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch Flexibility: Flexible Height: 0.890 inches after unrestricted recovery Color: Black Material: Plastic, polyolefin, rt-1304, raychem corp Material: Plastic, polyolefin, rt-1304, raychem corp **Style Designator:** Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

225.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5970-00-025-7939

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500