

View Online at https://aerobasegroup.com/nsn/5970-00-034-7084

New Online at https://defobdasegroup.com/nan/3370-00-034-7004
Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Large End Wall Thickness Of Main Body:
0.040 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.040 inches after unrestricted recovery
Distance From Intersecting Centerlines To Edge Of Small End:
1.540 inches after unrestricted recovery
Distance From Centerline Of Small End To Edge Of Large End:
1.250 inches after unrestricted recovery
Main Body Small End Inside Diameter:
0.840 inches as supplied
Main Body Large End Inside Diameter:
1.060 inches as supplied
Angle Between Large End And Small End Centerlines In Deg:
90.0 as supplied
Min. Tensile Strength (psi):
1500 pounds per square inch
Special Features:
Rail and channel assembly
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin, rt-301, raychem corp
Material:
Plastic, polyolefin, rt-301, raychem corp
Style Designator:
Boot-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Νο

NSN 5970-00-034-7084

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

