## NSN 5970-00-034-7090

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-034-7090 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Large End Wall Thickness Of Main Body: 0.040 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.040 inches after unrestricted recovery Distance From Intersecting Centerlines To Edge Of Small End: 2.540 inches after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 1.700 inches after unrestricted recovery Main Body Small End Inside Diameter: 0.890 inches as supplied Main Body Large End Inside Diameter: 1.300 inches as supplied Angle Between Large End And Small End Centerlines In Deg: 90.0 as supplied Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Rail and channel assembly Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Boot-90 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5970-00-034-7090

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500