NSN 5970-00-052-0693

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-052-0693

Reliability Indicator: Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Large End Wall Thickness Of Main Body: 0.050 inches as supplied Small End Wall Thickness Of Main Body: 0.050 inches after unrestricted recovery Distance From Intersecting Centerlines To Edge Of Small End: 2.900 inches after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 1.950 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.230 inches as supplied Main Body Large End Inside Diameter: 1.740 inches as supplied Angle Between Large End And Small End Centerlines In Deg: 90.0 as supplied Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Rail and channel assembly Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Boot-90 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5970-00-052-0693

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500