Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-052-4877

Re	liability Indicator:
Nc	ot established
0١	verall Length:
4.() feet
Те	mpurature Rating:
-5	5.0 degrees celsius and 135.0 degrees celsius
En	vironmental Protection:
Сс	prrosion resistant and flame resistant and mildew resistant and water resistant
Ex	panded Inside Diameter:
0.′	187 inches
Re	covered Inside Diameter:
0.0	093 inches
Re	covered Wall Thickness:
Be	tween 0.017 inches and 0.023 inches
He	eat Shrinkage Rating In Percent:
50	.0
En	d Application:
Mr	ap rg-31
De	esign Form:
Fu	ll round
Mi	n. Tensile Strength (psi):
15	00 pounds per square inch
Fle	exibility:
Fle	exible
Co	olor:
Ye	llow
Ma	aterial:
Pla	astic, polyolefin, mil-i-23053/5, class 1
Ма	aterial:
Pla	astic cross-linked polyolefin
St	yle Designator:
Sh	rinkable
Di	electric Material Voltage Rating Per Unit Thickness:
50	0.0 volts per military /0.001 inch/
Sh	elf Life:
N/	a
Ur	nit Of Measure:
De	emilitarization:
Nc	
Fii	g:
A2	2500